

# Orenda Startup Tank

## Parts List

- 25-50 ft. water hose (garden hose)
- Brass garden hose Y connector with valves
- 3/4" brass adapter swivel (female to female)
- 3/4" brass boiler drain valve (MIP & FIP x MHT)
- Stainless Steel Hose Clamp (1/2" band 1-3/4 to 2-3/4" diameter)
- Teflon Tape
- 3/4" 90° street elbow (male threaded to slip)
- 1-1/2" male threaded plug
- 1-1/2" 90° street elbow (male threaded to slip)
- 1-1/2" pool hose barb adapter (female threaded), 1-1/2" ID x 1-1/2" in FIP)
- 3 ft of 3/4" PVC pipe
- 1-1/2" MNPT x 3" TOE PVC threaded Pipe Nipple
- 12-15 ft pool vacuum hose
- Duct tape
- 1 zip tie
- Transmission fluid funnel with a flex spout
- 5-gallon bucket (for mixing)
- Empty water bottle to use as a float
- White tube sock or cloth

## Tools List

- PVC Glue and Primer
- PVC Saw
- Pliers
- Flat head screwdriver

### DISCLAIMER:

The fill tank needs to be built, maintained, and operated by a pool industry professional. These are Orenda Technologies recommendations but we are not liable for the use of calcium chloride and/or the build out or purchase of fill tanks. Calcium chloride, when mixed with water causes an exothermal reaction and gets extremely hot and can cause burns. Appropriate eye and skin protection should be worn while handling chemicals. Individuals and/or companies building and/or use the fill tank at their own risk/liability.

## Startup Tank Overview

[www.orendatech.com](http://www.orendatech.com)



orenda<sup>®</sup>  
technologies

